



LAPI LABORATORIO PREVENZIONE INCENDI S.p.A.
Sede Primaria: I-59100 PRATO - Via della Quercia, 11
Telefono +39 0574.575.320 - Telefax +39 0574.575.323
Sede Secondaria: I-50041 CALENZANO (FI) - Via Petrarca, 48
e-mail: lapi@laboratoriolapi.it
web site: www.laboratoriolapi.it

Reg. 305/2011
Notified Body N°0987



Certificate of evaluation and verification of constancy of performance **0987-CPR-196 Rev. 1**

in compliance with the Regulation UE 305/2011 on the approximation of law, regulations and administrative provisions of the Member States relating to the construction products, it has been stated that the construction product :

the building products denominated:
PURICOMPACT SUPER B1 - PURICOMPACT STAR 2 B1

Description of the product:
HPL composite laminate used for internal and external wall and ceiling covering, thickness from 6,0 mm. to 20,0 mm enclosed, various colours

Type: HPL laminate
Use: Internal and external covering of wall and ceiling

Produced by:
PURICELLI S.r.l.
Via Nuova Valassina, 3 - 23845 COSTA MASNAGA (LC) - ITALY

in the factory of:
Via Nuova Valassina, 3 - 23845 COSTA MASNAGA (LC) - ITALY

is submitted by the manufacturer to the factory production control (FPC) under **system 1** and to the testing of samples (ITT) by the Notified body for Certification, Inspection and Testing according to Regulation UE 305/2011.

The Notified Body (**LAPI SpA - Laboratorio Prevenzione Incendi N° 0987**) has performed the initial type testing on the samples taken at the factory in accordance with the described test for the relevant characteristics of the product, the initial inspection of the factory and the factory production control and it will perform the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning to the **System 1** and the performances described in Annex ZA of the standard
EN 438 – 7: 2005

High-pressure decorative laminates (HPL) - Sheets based on thermosetting resins (usually called laminates) - Part 7: Compact laminate and HPL composite panels for internal and external wall and ceiling finishes

are performed and the product complies with characteristics required as for:

- **Release of formaldehyde class: E1**
- **Durability: Resistance to wet conditions - rating 5**
- **Resistance to climatic shock - rating 5**
- **Resistance to fixings: 2000 N (6mm) – 3000 N (8 mm) - 4000 N (≥ 10 mm)**

Moreover the product, tested and evaluated according to Annex B of the product standard EN 438-7:2005 has reaction-to-fire Euroclass classified according to UNI EN 13501-1:2009

B-s1,d0

This result is valid in the following conditions:

- External internal use.
- Covering of wall and ceiling, internal and external, fixed on metallic frame with or without interposition of rockwool complying with EN 438-7 Annex B.2.; horizontal and vertical junctions have been covered with an aluminium plate, width 25 mm and thickness 2 mm



This certificate, first time issued on 16/12/2013 and previously revised on 28/11/2017, has been released on 16/12/2018 and it remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or as long as the factory production control itself are not modified significantly and latest on 15/12/2023.

Note: this Revision 1 of the document has been issued without any test repetition, only for the correction of the date of expiry, erroneously indicated in the document 0987-CPR-196.

Prato, 18/04/2019

The Technical Director
Dr. Luca Ermini